



298.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Celeron Processor BayTrail-M N2910/N2920
- 2 *DDR3L 1066MHz Single CH SO-DIMM up to 8GB
- Support 2 * Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- Integrated 1 * 24-bits Dual CH LVDS
- Supports 1 * Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- Support Watch dog Technology
- Thin Mini-ITX Form Factor(17cm x 17cm)
- Slim & Fanless design, within 2cm height

| | |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU | • Intel Celeron Processor BayTrail-M N2910/N2920 |
| Chipset | • INTEL® Bay Trail-M SoC Processor |
| Memory | • 2 *DDR3L 1333/1066MHz Single CH SO-DIMM up to 8GB |
| Expansion Slots | • 1 * PCI-E x 1 slot • 1 * MINI PCI-E |
| Storage | • 2 * Serial ATAll (3Gb/s) connectors (One share with mSATA) • 1 * mSATA socket (Share with one SATA port) |
| Audio | • Realtek ALC662 2-Channel HD Audio |
| Ethernet LAN | • 1 * RTL8111G PCI-E Gigabit LAN |
| LVDS | • 1 * 24-bits Dual CH LVDS connector |
| USB | • Embedded 3 * USB 3.0 + 5 * USB 2.0/1.1 |
| Special Features | • Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog |
| Rear Panel I/O | • 1 * USB 3.0 port • 3 * USB 2.0/1.1 ports • 1 * RJ-45 port • 1 * DVI-I port • 1 * COM port (Support RS232/422/485) • 1 * Line-out connector • 1 * 4-pin 9V~36V DC in jack |

| | |
|-------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • Internal I/O | <ul style="list-style-type: none"> • 1 * USB 3.0 header for 2 USB 3.0 ports • 1 * USB 2.0/1.1 header for 2 USB 2.0 ports • 1 * KB/MS header • CPU smart Fan / System Fan headers • 1 * LVDS header & 1 * GPIO header & 1 Parallel header • 3 * COM headers & 4 * COM ports 5V/12V Selectable headers • 1 * AUDIO AMP & 1 * AUDIO header & 1 * SPDIF header • 1 * chassis intrusion header & 1 * AT mode selectable header |
| <ul style="list-style-type: none"> • BIOS | <ul style="list-style-type: none"> • AMI 64MB SMT Flash ROM |
| <ul style="list-style-type: none"> • Form Factor | <ul style="list-style-type: none"> • Thin Mini ITX Form Factor (170mm x 170mm) |
| <ul style="list-style-type: none"> • Functional | <ul style="list-style-type: none"> • Panel PC, ATM, Security, KIOSK, POS, General Application, Transportation |
| <ul style="list-style-type: none"> • Certificate | <ul style="list-style-type: none"> • CE, FCC, RoHS |
| <ul style="list-style-type: none"> • Temperature | <ul style="list-style-type: none"> • Operating within 0~60 centigrade • Storage within -20-85 centigrade |