

889.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® Haswell / Broadwell SoC Processor
- 2\* DDR3L 1333/1600 up to 16GB
- Support 1 \* Serial ATAPI (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 \* 24 bits Dual Channel LVDS header
- 1 \* mPCIE
- 1 \* mSATA (share with mPCIE)
- 2 \* USB 2.0 + 4 \* USB 3.0
- 2 \* HDMI Output
- Supports 2 \* Gigabit LAN
- Support CPU Smart FAN
- DC IN Jack 9~24V

|                     |  |
|---------------------|--|
| • Dimension (W*H*D) | • 185 * 60 * 142 mm  |
| • Construction      | • Aluminum housing   |
| • Colors            | • Black  |
| • MB model          | • JNF3E-4300U (3.5" SBC)   |
| • CPU & CHIP        | • INTEL® Haswell ULT i5-4300U  |
| • BIOS              | • AMI 32MB SMT Flash ROM   |
| • Memory            | • 2 * SO-DIMM (DDR3-1333/1600Mhz_Max 16GB)   |
| • Storage Space     | • 1 * 2.5" SATA Device (Support SATA 6G / Max Height 9.5 mm)<br>• 1 * m-SATA SSD Device (Mini PCI-E) |
| • Display Interface | • 2 * HDMI<br>• 1 * LVD-24 bits ( Internal pin header)   |

|                       |  |
|-----------------------|--|
| • Network             | <ul style="list-style-type: none"> <li>• 2 * RJ45 (I211AT + I218LM Gigabit LAN)</li> <li>• WiFi (optional / JBC382F3EW-4300UB)</li> </ul>  |
| • Audio               | <ul style="list-style-type: none"> <li>• 1 * Audio</li> </ul>  |
| • Front I/O Port      | <ul style="list-style-type: none"> <li>• 2 * USB 2.0</li> <li>• 4 * COM</li> </ul>   |
| • Rear I/O Port       | <ul style="list-style-type: none"> <li>• 4 * USB 3.0</li> <li>• 2 * USB 2.0</li> </ul>   |
| • Expansion Interface | <ul style="list-style-type: none"> <li>• 1 * Mini PCI-E (Half-size)</li> </ul>   |
| • Power Source        | <ul style="list-style-type: none"> <li>• DC-12V Jack input</li> <li>• Adapter : AC_90~240V / DC_12V_5A / 60W</li> </ul>  |
| • Certification       | <ul style="list-style-type: none"> <li>• EMC : CE , FCC</li> <li>• Safety : RoHS , ErP</li> </ul>  |
| • Environment         | <ul style="list-style-type: none"> <li>• Operating Temperature : 0 ~ 50■</li> <li>• Storage Temperature : 0 ~ 60■</li> <li>• Vibration During Operation : N/A</li> <li>• Shock During Operation : N/A</li> </ul> |
| • Mounting            | <ul style="list-style-type: none"> <li>• Wall mounting Kits</li> </ul>   |
| • Packing             | <ul style="list-style-type: none"> <li>• Net Weight■2.2KG</li> <li>• Gross Weight■3.5KG</li> <li>• Color Box Dimension■250(W) x 118 (D) x 295 (H) mm</li> </ul>  |