



1469.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- i5-1135G7 !
- 17" Panel Computer !

- 17.0" 350 nits TFT LCD with LED backlight
- 10 points Multi Capacitive Touch
- Support Open frameless design
- A true Flat, easy to clean front surface with edge to edge design
- Front IP65 for protection against water and dust
- Aluminum Die-Cast Panel PC series, support for easy HDD and DARM installation
- Support Cable less design
- 12 36V DC input Support, with Electrical Over Stress(EOS), OVP design
- VESA Support 100x100mm

|             |   |  |
|-------------|---|--|
| Model       | - HPC170C-DCP1135G7   |  |
| Main System | - Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor<br>- 2* DDR4 SO-DIMM (Max 64GB)<br>- 256MB SPI Flash ROM<br>- Watchdog Timer 256 levels, 0~255 sec. |  |

|               |  |
|---------------|--|
| Display       | <ul style="list-style-type: none"> <li>- IP65, NEMA 4 rugged protection, metal front bezel</li> <li>- 17.0" With LED Backlight</li> <li>- 350 nits</li> <li>- 16.7m display color</li> <li>- 1280 x 1024 @60Hz resolution</li> <li>- 170°/160° viewing angle (H/V)</li> <li>- 0.264 x 0.264mm pixel pitch</li> <li>- 4:3 aspect ratio</li> <li>- 1000:1 contrast ratio</li> <li>- 3.5ms response time</li> </ul> |
| Touch Screen  | <ul style="list-style-type: none"> <li>- Projected capacitive type</li> <li>- 372.92 x 305.34mm ±0.3mm active range</li> <li>- Transparency ■ 85%</li> <li>- Surface Hardness ■ 6H (JIS-5400)</li> </ul>   |
| I/O Connector | <ul style="list-style-type: none"> <li>- 2* USB3.2 (Gen. 2)</li> <li>- 4* USB2.0</li> <li>- 2* RS232/422/485</li> <li>- 2* RS232 (option 16bit GPIO)</li> <li>- 1* HDMI</li> <li>- 1* AT/ATX Mode Button</li> <li>- 2* RJ45 (1* Intel® I225-V 2.5GbE, 1* Intel® I219LM GbE)</li> <li>- 1* 12~36V DC-in Locking Jack</li> <li>- 1* Power button</li> <li>- 1* 2pin Front Power button</li> </ul>                  |
| Storage       | <ul style="list-style-type: none"> <li>- 1* 2.5" SATA HDD</li> <li>- 1* M.2 M key (2242/2280, PCI-Ex4)</li> </ul>  |
| Expansion     | <ul style="list-style-type: none"> <li>- 1* M.2 E key (2230) for WIFI</li> <li>- 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)</li> </ul>   |
| Case          | <ul style="list-style-type: none"> <li>- Aluminum panel</li> <li>- Iron case</li> <li>- White color</li> <li>- Spray paint coating requirement</li> </ul>  |
| Power         | <ul style="list-style-type: none"> <li>- AC version: 100~240V AC-DC 60W power adapter or</li> <li>- DC version: 12VDC with over current protection fuse</li> <li>- Consumption: 47.5W</li> </ul>   |
| Compliance    | <ul style="list-style-type: none"> <li>- CE, FCC, IP65 (Front), Option</li> </ul>  |
| Safety        | <ul style="list-style-type: none"> <li>- Shock: 1ms duration</li> <li>- Vibration: 5~500Hz/1 Grms</li> </ul>   |
| Dimensions    | <ul style="list-style-type: none"> <li>- 400.9 x 333.3 x 65.0mm</li> </ul>   |
| Temperature   | <ul style="list-style-type: none"> <li>- Operating Temperature: -10 ~ 60° C</li> <li>- Storage Temperature: -20 ~ 70° C</li> <li>- Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>  |