



999.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron-M/Pentium-M
- Integr. Automotive PSU
- PCMCIA

**CARTFT.COM**

**Support:**  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

As an additional highlight this barebone offers a PCMCIA slot.

| CALU specifications          |                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Processor (supported)</b> | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher                                                                                                                                                                                                                                                                      |
| <b>Memory</b>                | Supports DDR 400/333/266 DIMM RAM<br>0.8" low profile<br>2x memory slots !<br>Maximum : 2 GB                                                                                                                                                                                                                                                              |
| <b>Video</b>                 | Intel Extreme Graphics 2<br>Supports up to 64MB DVT video memory                                                                                                                                                                                                                                                                                          |
| <b>Audio</b>                 | Software AC '97 Audio CODEC                                                                                                                                                                                                                                                                                                                               |
| <b>Peripheral Connection</b> | Front :<br>1 x PCMCIA Slot<br>1 x IEEE 1394 Firewire port<br>1 x MIC Port<br>1 x Ear Phone output Jack<br>Power-on button<br>Reset button<br>Power-on and HDD LED<br><br>Rear :<br>1 x RS232 COM port<br>1 x parallel printer port<br>1 x RJ45 10/100Mb Fast Ethernet<br>1 x Line-Out output Jack<br>2 x USB 2.0 / 1.1 Ports<br>1 x 15 pin VGA<br>1 x DVI |
| <b>Storage</b>               | One 2.5 inch Hard Disk and 9.5mm high.<br>(Support Ultra DMA 33/66/100).                                                                                                                                                                                                                                                                                  |
| <b>Weight &amp; Size</b>     | System approximately 3kg (fully equipped).<br>System Dimension: 155 x 255 x 55 mm                                                                                                                                                                                                                                                                         |
| <b>Power req.</b>            | 9-16V, 5A                                                                                                                                                                                                                                                                                                                                                 |

---

**Accessory**

|                        |                                                           |
|------------------------|-----------------------------------------------------------|
| <b>Storage</b>         | Supports all 2.5" standard IDE hard drive, ATA-100/66/33. |
| <b>Scope of supply</b> | Connector cable for Plus, ignition plus and ground        |
|                        | Barebone                                                  |
|                        | CPU Kühlkörper                                            |

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)